



## Yuasa Technisches Datenblatt

### Yuasa YBX5100 - YBX5000 Silver High Performance SMF Batterien

#### Leistung

Spannung	12V
Kapazität 20 Std (vorgegeben)	75Ah
Kaltstartstrom (A) EN1	710A

#### Abmessungen

Länge	278mm
Breite	175mm
Höhe	175mm

#### Maße und Gewichte

Durchschnittliches Gewicht inkl. Säure	17.6kg
--	--------



#### Gehäuseeigenschaften

Gehäusotyp	LB3 DIN
Batteriehälter	B3/B4
Ladezustandsanzeige	✓
Tragegriffe	✓
Entgasung	✓
Deckel Typ	SMF doppelwandige Deckelkonstruktion

#### Technologie

Flammschutz	✓
Technologie	Ca/Ca
Separator	PE
VDA Überroll Test	✓
Ladestrom	4A
Performance Marking	W4-C2-V3-E1



#### Anschlusspol Typ

#### Zellenanordnung


#### Batteriehälter

##### T1

Standard DIN Post



B3/B4 (B3 with Hold-Down adaptor)



Ausstellungsdatum: 18/09/2019 - E&EO



## Yuasa Technical Data Sheet

### Yuasa YBX5100 - YBX5000 Silver High Performance SMF Batteries

#### Performance

Voltage	12V
Capacity (20-hour)	75Ah
Cold Cranking Amps (EN1)	710A

#### Dimensions

Length	278mm
Width	175mm
Height	175mm

#### Weights & Measures

Mean Weight with Acid	17.6kg
-----------------------	--------



#### Container Features

Case Type	LB3 DIN
Hold Down	B3/B4
State of Charge Indicator	✓
Handles	✓
End Venting	✓
Lid Type	SMF Double Lid


#### Technology

Flame Arrestor	✓
Technology	Ca/Ca
Separator	PE
VDA Roll Over Test	✓
Recommended Charge Rate	4A
Performance Marking	W4-C2-V3-E1


#### Terminal Type

##### T1

Standard DIN Post




#### Cell Assembly Layout



#### Battery Hold-down

B3/B4 (B3 with Hold-Down adaptor)



Data Sheet generated on 18/09/2019 - E&OE